


Encl

1621

4296-121 US

The undersigned certifies that this communication is being deposited with the United States Postal Service as prepaid first class mail in an envelope addressed to Commissioner of Patents, Mail Stop: Non-Fee Amendment, P.O. Box 1450, Alexandria, VA 22313-1450 on April 8, 2004.


Gregory C. Houghton

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of :
Matsumoto, Y. et al. :
Serial No. 09/652,209 : Group Art Unit: 1621
Filed: August 30, 2000 : Examiner: Wachtel, Alexis A
For: REACTOR FOR CATALYTIC :
GAS PHASE OXIDATION :

Commissioner for Patents
Mail Stop: Non-Fee Amendment
P.O. Box 1450
Alexandria, VA 22313-1450

SIR:

AMENDMENT AND REQUEST FOR RECONSIDERATION

This Reply is submitted pursuant to the Office Action mailed January 12, 2004, to which a Reply is due April 12, 2004. Reconsideration of the present rejections and withdrawal of the present rejections are respectfully requested. Claims 1-19 are under consideration.

the shell, and a cross sectional area of holes in the donut type baffle plates in the range of 2 – 25% of the cross sectional area of the shell.

6. (Currently amended) A reactor according to claim 3, wherein ~~a difference in the number of reaction tubes configured in the regions of reaction tubes divided by a least two circulation passages~~ a value calculated by $|(\text{Number of reaction tubes in individual regions}) / (\text{average number of reaction tubes in the regions}) - 1| \times 100$ is within 3%.

7. (Currently amended) A reactor according to claim 4, wherein ~~a difference in the number of reaction tubes configured in the regions of reaction tubes divided by at least two circulation passages~~ a value calculated by $|(\text{Number of reaction tubes in individual regions}) / (\text{average number of reaction tubes in the regions}) - 1| \times 100$ is within 3%.

8. (Original) A reactor according to claim 4, wherein a cross-sectional area of the circulation passage is in the range of 0.5 – 5% based on the cross-sectional area of the shell.

9. (Original) A reactor according to claim 5, further comprising at least one circulation passage for the heating medium between an empty space devoid of a configuration of reaction tubes in the center of the shell and the peripheral part of the shell.

10. (Original) A reactor according to claim 7, wherein a cross sectional area of the empty space is in the range of 0.5 – 5% of the cross sectional area of the shell, a cross sectional area of the disc type baffle plates in the range of 50 – 95% of the cross sectional area of the reactor, and a cross sectional area of holes in the donut type baffle plates in the range of 2 – 25% of the cross sectional area of the shell.

11. (Original) A reactor according to claim 1 further comprising at least two of circulation conduits for supplying or withdrawing the heating medium to or from the shell.

12. Cancelled.

13. (Currently amended) ~~A reactor according to claim 1, wherein the circulation conduit further has~~ A shell-and-tube type reactor comprising:

a cylindrical shell having disposed on the periphery thereof a plurality of annular conduits for guiding a heating medium in or out in the radial direction and having a raw material inlet and a product outlet;

a circulation device for mutually connecting a plurality of annular conduits;

a plurality of reaction tubes constrained to the reactor by a plurality of tube sheets;